

Cod: 95841754021006

Smeg FD526DS Topline Series raised washer-dryer with 500x500 mm basket 7 Kw with softener



Description

Professional front-loaded, raised, 500 mm basket, double-walled, detergent dispenser, softener, suitable for washing 600x400 mm GN1/1 trays Structure: AISI 304 double-walled stainless steel with insulation Control panel: touch No. of programmes: 14 Hour baskets: 72/60/50/40/30/24/15/3 Basket dimensions: 500x500 mm Useful load height: 415 mm Rinse aid dispenser: electronically controlled peristaltic pump Detergent dispenser: electronically controlled peristaltic pump Thermal-acoustic insulation: door and washing chamber Softener: Integrated Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel Washing system: Washing pump with 'Soft Start' system Washing pump power: 1 kW Drain system: Drain pump for partial outflow of wash water, inspectable Filter system: Three-stage filtration integrated with the drain pump for separation of residues and control of the water level in the tank Rinsing system: rinse pump and atmospheric boiler (HTR System) Tank heating element: 0.8 kW Boiler heating element: 6.00 kW / 2.00 kW single-phase Lower compartment size: 560x320mm TOTAL RINSING' function of the water in the tub after each wash EXTRA RINSE' function for prolonged rinsing Double-walled, balanced, insulated and gasketed door Automatic cycle start when door is closed (selectable) Double-walled tank with rounded corners Insulated boiler Crystal cycle with reduced rinse

temperature ULTRA CLEAN PRO cycle for sanitising dishes Selectable 'Drain and clean tank' cycle Mains non-return device Thermostop for rinsing water temperature control Self-diagnosis system with fault indication Filter positioning control system Heating element 'Stand-by' function during periods of non-use

Dimensions

Dimensioni esterne	600x600x1350 mm
--------------------	-----------------

Technical data

Alimentazione	Electric
Capacità	11 Lt
Capacità boiler	6 Lt
Consumo d'acqua	2.7 kg
Frequenza	50 Hz
Materiale	aisi 304 stainless steel
Potenza Elettrica	7 kW
Voltaggio	230 V, 400 V

Standard equipment

In dotazione	Cesto universale con fondo piano per 18 piatti
--------------	--